



August 8, 2025

Cleaning Instructions for All Hebron Brick Company Clay Masonry Products

Hebron Brick Company has tested and approved the following cleaning solutions for use on Hebron Brick Clay Masonry products. Click the product name to download the product specifications and cleaning instructions.

[Prosoco Sure Klean® Vana Trol®](#)

[Diedrich 202V Vana-Stop](#)

[Eaco Chem NMD 80](#)

Additional Information

1. Bricks should not be placed directly on the ground at the job site. Protective material should be provided when brick are unloaded. In the case of white, buff, tan, grey, brown or black bricks, complete protection should be provided until used.
2. Protect the wall as work progresses. This includes protecting the base of the wall after the first course of brick is laid and protecting the wall from rain and snow to keep excessive water out of the wall. Cover the tops of the walls and window and door sills at the end of each day's work. It is particularly important to protect sills after the windows have been set but not caulked.
3. Scaffolding should be set far enough away from the wall to allow mortar droppings to fall to the ground. At the end of each workday the scaffold boards closest to the wall should be tilted up and away from the wall to dump excess mortar droppings and prevent rainfall from splashing mortar onto the masonry.
4. Removed excess mortar with stiff bristle brushes or wood or plastic scrapers as the work progresses.
5. Sand and water used in the mortar should be free of mud, salts and debris which may cause efflorescence or staining. If you don't drink the water, don't put it in the mortar mixer!

Note: Because of the extensive variety of applications, job conditions, and cleaning methods available for use with clay masonry, these recommendations do not eliminate the need to test chemicals and procedures for every project. Other cleaning solutions are available for remedial cleaning. Contact your distributor or Hebron Brick Technical Services at (701) 232-0781. Reactions of solutions with materials other than the listed brick are not the responsibility of Hebron Brick Company.

IMPORTANT!

**Do not pressure wash sand-coated brick.
Do not clean brick with muriatic acid.**